

FICHA TÉCNICA - TECHNICAL SHEET - FICHE TECHNIQUE
DESCRIPCIÓN DEL PRODUCTO - PRODUCT DESCRIPTION - DESCRIPTION PRODUIT

MODELO : 461450/PE100

ENVASE DE ALUMINIO : INTERIOR: Desnudo
EXTERIOR: Desnudo


DIMENSIONES DEL PRODUCTO- PRODUCT DIMENSIONS - DIMENSIONS PRODUIT

DIMENSIONES - dimensions - dimensions		
SUPERIOR EXTERIOR - top out - Extérieur supérieur	Ø 205	mm
FONDO - bottom - fond	Ø 168	mm
ALTURA - depth - hauteur	57	mm
CAPACIDAD - volume - volume	1450	ml

CARACTERÍSTICAS DEL MATERIAL - MATERIAL SPECIFICATION - SPECIFICATION MATIERE

LUBRICANTE - Lubricant - Lubrifiant	0,2-0,5 g/m2
MATERIAL - material - matiere	Aluminio
ALEACIÓN - alloy - alliage	Serie/s:3000 or 8000
ESPESOR - thickness - épaisseur	50±8% μ
LACA INTERIOR - lacquering inside- lacque intérieur	g/m2
LACA EXTERIOR - lacquering outside- lacque Extérieur	g/m2

PESO - WEIGHT- POIDS

	Minimum	Nominal	Maximum	
Peso unitario - unit weight - unité de poids	9,71	10,55	11,39	g/container

EMBALAJE - PACKAGING - CONDITIONNEMENT

EMBALAJE PRIMARIO - primary packaging - conditionnement premier	BOLSA DE POLIETILENO		
EMBALAJE SECUNDARIO - secondary packaging - conditionnement secondaire	NS600		
DIMENSIONES - dimensions - dimensions	CAJA CARTON 620 X 375 X 420	mm	
CAJAS /PALET -boxes / pallet - cartons / palette	20	units	
UNIDADES POR CAJA/JAULA- Units per box / cage - unités d'emballage	600	units	
CONDICIONES DE ALMACENAJE - Storage conditions - Conditions de stockage	8 - 30 °C, máx. 50% rH		

REMARKS: Our acknowledgement presupposes that the packaging material is appropriately processed. Please, be advised that the storage of strongly acidic or alkaline products in direct contact with uncoated aluminium foil should be avoided. In aqueous environment these products can dissolve aluminium, the extent of which would depend on temperature and contact time. The suitability of uncoated aluminium foil for specific applications should be ascertained by the relevant manufacturer / packer.