

**FICHA TÉCNICA - TECHNICAL SHEET - FICHE TECHNIQUE**

**DESCRIPCIÓN DEL PRODUCTO - PRODUCT DESCRIPTION - DESCRIPTION PRODUIT**

**MODELO :** 460980/PE100

**ENVASE DE ALUMINIO :** INTERIOR: Desnudo  
EXTERIOR: Desnudo



**DIMENSIONES DEL PRODUCTO- PRODUCT DIMENSIONS - DIMENSIONS PRODUIT**

DIMENSIONES - dimensions - dimensions		
SUPERIOR EXTERIOR - top out - Extérieur supérieur	Ø 205	mm
FONDO - bottom - fond	Ø 176	mm
ALTURA - depth - hauteur	36	mm
CAPACIDAD - volume - volume	980	ml

**CARACTERÍSTICAS DEL MATERIAL - MATERIAL SPECIFICATION - SPECIFICATION MATIERE**

LUBRICANTE - Lubricant - Lubrifiant	0,2-0,5 g/m2
MATERIAL - material - matiere	Aluminio
ALEACIÓN - alloy - alliage	Serie/s:3000 or 8000
ESPESOR - thickness - épaisseur	50±8% μ
LACA INTERIOR - lacquering inside- lacque intérieur	g/m2
LACA EXTERIOR - lacquering outside- lacque Extérieur	g/m2

**PESO - WEIGHT- POIDS**

	Minimum	Nominal	Maximum	
Peso unitario - unit weight - unité de poids	8,04	8,73	9,43	g/container

**EMBALAJE - PACKAGING - CONDITIONNEMENT**

EMBALAJE PRIMARIO - primary packaging - conditionnement premiér	BOLSA DE POLIETILENO
EMBALAJE SECUNDARIO - secondary packaging - conditionnement secondaire	CAJA CARTÓN
DIMENSIONES - dimensions - dimensions	CAJA CARTON 620 X 375 X 420 mm
CAJAS /PALET -boxes / pallet - cartons / palette	20 units
UNIDADES POR CAJA/JAULA- Units per box / cage - unités d'emballage	600 units
CONDICIONES DE ALMACENAJE - Storage conditions - Conditions de stockage	8 - 30 °C, máx. 50% rH

**REMARKS:** Our acknowledgement presupposes that the packaging material is appropriately processed. Please, be advised that the storage of strongly acidic or alkaline products in direct contact with uncoated aluminium foil should be avoided. In aqueous environment these products can dissolve aluminium, the extent of which would depend on temperature and contact time. The suitability of uncoated aluminium foil for specific applications should be ascertained by the relevant manufacturer / packer.